



## Características técnicas:

**Chips LED:** .....Philips / Osram - 2835  
**Temperatura color:** ..... 3000K / 4000K / 5000K / 5700K / 6500K  
**Drivers:** ..... Philips / LIFUD / BOKE  
**Regulación:** ..... 0-10V / PWM / Timer / DALI  
**Voltaje:** ..... 200-240V  
**Factor de potencia:** ..... > 0,9  
**Difusor:** ..... PS  
**Materiales:** ..... Marco AL / Carcasa trasera PET 3mm  
**Protección (IP):** ..... IP20 / IP54 / IP66  
**Deslumbramiento:** ..... UGR <19 / UGR < 22  
**Vida útil (L80B10) Ta 25°C / Garantía:** ..... 35.000 ~ 100.000 horas / 3 ~ 10 años  
**Certificaciones:** ..... **CE ROHS**

| Modelo      | Potencia | LED Qty | Apertura | LM / W | Tamaño (mm)     |
|-------------|----------|---------|----------|--------|-----------------|
| CP6060-40WD | 40W      | 48      | 120°     | >120   | 595 x 595 x 30  |
| CP6060-48WD | 48W      | 48      |          | >120   | 595 x 595 x 30  |
| CP1230-40WD | 40W      | 48      |          | >120   | 1195 x 295 x 30 |
| CP1260-60WD | 60W      | 96      |          | >120   | 1195 x 595 x 30 |